




**12**  
Watts



## PARAMETERS

ITEM NO

GLS-7226X

<b>Solar Panel</b>	18V/28W Monocrystalline Solar Panel. Grade A
<b>LED</b>	12W, 10*18mil Epistar Chip
<b>Lifespan of LED</b>	More than 50,000 hours
<b>Luminous Flux</b>	1200lm~1320lm
<b>Color Temperature</b>	3500~7500K
<b>Beam Angle</b>	120°
<b>Battery</b>	12V/14AH Li-ion Lithium Battery    12.8V/12AH LiFePO4 Lithium Battery
<b>Discharging Time</b>	18h (100% power) 42h(energy-saving mode)
<b>Charging Time</b>	9h(AM 1.5, 1000W/m <sup>2</sup> ,25°C
<b>Material</b>	6063 Aluminum, PC
<b>Working Temperature</b>	-25°C~55°C
<b>Protection Grade</b>	Ip65
<b>Product Size</b>	Φ510*750*250mm
<b>Package Size</b>	780*570*300mm
<b>Number of Packing</b>	1 set/carton
<b>Net Weight</b>	8.4KG
<b>Gross Weight</b>	10.3KG
<b>Diameter of Mounted Lamppost</b>	76mm
<b>Control Mode Light</b>	Control + Time Control
<b>Package Quantity</b>	196 sets/20GP, 469 sets/40HQ

Suggest Height  
**2.5m~3m**



**IP 65**

